



- Suitable for occupied areas
- Discharge time: 10 seconds
- No residue to clean up after discharge
- Widely accepted as substitute to Halon 1301
- Compliance with standards ISO14520 and NFPA.2001
- Suitable for storage in welded high pressure cylinders, saving space and money
- Electrically non - conductive
- Global Warming Potential of 1
- Zero Ozone Depletion Potential

A wide field of application

NOVEC 1230

NOVEC 1230 extinguishing agent is a clean gas widely accepted as substitute to Halon. NOVEC 1230, or dodecafluoro-2-methyl pentan-3-one ($\text{CF}_3\text{CF}_2\text{C}(\text{O})\text{CF}(\text{CF}_3)$), is suitable for the protection of most hazards where Halon 1301 had to be applied in the past. Because NOVEC 1230 is not electrical conductive, (but it is odourless and colourless), it is effective in the protection of electrical hazards, such as computer rooms.

Furthermore, it is suitable for class A fires (fires including solid materials) as well as for class B fires (flammable liquids).

NOVEC 1230 extinguishes fires mainly by physical means, weakening and extinguishing the fire by absorbing heat.

Once discharged, NOVEC 1230 extinguishes the fire quickly reducing to a minimum damages to property and valuable equipment, likewise ensuring total safety to persons.



LPG systems containing NOVEC 1230 are designed to discharge within 10 seconds. Extinguishing agent pressurized with dry Nitrogen at 24 or 41 bar and stored in steel cylinders fitted with approved valves.

Where To Use It

Typical applications:

- With electrical or electronic equipment
- Archives
- Stores
- Cable ducts
- Engine rooms
- Flammable liquids
- Hazards with people inside



Physical Properties

Chemical name	Dodecafluoro-2-methylpentan-3-one
Chemical formula	CF ₃ CF ₂ C(O)CF(CF ₃) ₂
Compliance with ISO 14520, UNE 23570 and NFPA 2001	FK-5-1-12
Molecular weight	316.04
Boiling point at 1.013 bar	49.2°C
Liquid density at 20°C	1,616 g/ml
Critical temperature	168.66°C
Critical pressure	18.646 bar
Vapour pressure at 20°C	0.3260 bar
Relative electrical resistance at 1 atm. 25°C (N ₂ =1.0)	20
Maximum filling density	1.48 kg/l
Design concentration for heptane	5.9%
Flooding factor for heptane at 20°C	0.8723 kg/m ³
Design concentration for surface fires class A	5.3%*
Flooding factor for surface fires class A	0.7786 kg/m ³
NOAEL	10%
LOAEL	>10%
Ozone depletion potential	0
Greenhouse effect potential	1

* According to ISO 14520



HEAD OFFICE

Mestre Joan Corrales 107-109
08950 Espulgues de Llobregat
Barcelona (España)
Tel.: +34 93 4802933
Fax: +34 93 4737492
e-mail: export@lpg.es
http://www.lpg.es

LPG RUSSIA

Moscow 117419
2-Rozhinskiy proezd, D.8,
stroynie 4
Tel.: +7 095 998 90 93
Mobile: +34670 33 9651
e-mail: acardoso@mail.ru

LPG PORTUGAL

Casais da Serra,
Zona Industrial, Lote 4
2665-305 Milharado
Portugal
Tel.: +351 21 9751322/3
Fax: +351 21 9751317
e-mail: lpg.portugal@mail.telepac.pt

LPG MIDDLE EAST

P.O. BOX 2367
JEDDAH 21436
KSA
Tel.: +966 2 6637017/53
Fax: +966 2 6690741
e-mail: lpg@lpgme.com
http://www.lpgme.com

LPG FRANCE

Z.I. Les Béthunes
13/14 Rue du Compas
Saint-Ouen L'Aumône, B.P. 9142
95074 Cergy Cedex - France
Tel.: +33 1 34219388
Fax: +33 1 30373185
e-mail: lpg.france@free.fr

LPG TÜRKIYE

Yenişehir Mah. 24. Sokak
Koru Sitesi C Blok KAT 6, D:25
81520 Pendik - İstanbul
Türkiye
Tel.: / Fax: +90 216 4821831
Mobile: +90 532 4263524
e-mail: lpg@lpgtr.com

LPG FIRE Ltd.

5-7 Top Angel
Buckingham Industrial Park
Buckingham
MK18 1TH (UK)
Tel.: +44 1280 821229
Fax: +44 1280 821239
e-mail: tnichols@lpg.es

LPG AMÉRICA LATINA

Juan Benito Blanco 3301-3303
Apartamento 302
11.300 Montevideo
Uruguay
Tel.: +598 2 6227840
Fax: +598 2 6229801
e-mail: lpg.uruguay@conectate.com.uy